

FLAGPOLE TRUCKS & ACCESSORIES



ST-1 SERIES

Cast aluminum construction with a 1" outside diameter nylon pulley on a 3/16" stainless steel axle. Designed to slip over the top of the flagpole and be secured by one 1/4"-20NC stainless steel set screw. The top is designed to accept an ornament with a spindle threading of 1/2"-13NC as standard but can be supplied with other sizes of threading if desired. The ornament is secured to the truck with a size 10-32 stainless steel pan head screw. Maximum halyard diameter is 1/4".

For External Halyard Poles • Cap Style • Stationary • Single Pulley

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
ST-1-38	1 ³ / ₈ "	1.0	340000	\$23	\$21	340005	\$26	\$24	340010	\$26	\$24	340015	\$26	\$24
ST-1-12	1 ¹ / ₂ "	1.0	340001	23	21	340006	26	24	340011	26	24	340016	26	24
ST-1-34	1 ³ / ₄ "	1.0	340002	23	21	340007	26	24	340012	26	24	340017	26	24
ST-1-16	1 ⁵ / ₁₆ "	.80	340003	23	21	340008	26	24	340013	26	24	340018	26	24
ST-1-20	2"	.80	340004	23	21	340009	26	24	340014	26	24	340019	26	24



ST-32 SERIES

Cast aluminum construction with a 1⁷/₁₆" outside diameter cast pulley on a 1/4" stainless steel axles. Designed to slip over the top of the flagpole and be secured with three 5/16"-18NC stainless steel set screws. The top is designed to accept an ornament with a spindle threading of 1/2"-13NC as standard but can be supplied with other sizes of threading if desired. The ornament is secured to the truck with a 1/4"-20NC stainless set screw. Maximum halyard diameter is 5/16".

For External Halyard Poles • Cap Style • Stationary • Double Pulley

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
ST-3	1 ⁷ / ₈ "	1.9	340040	\$47	\$42	340042	\$51	\$47	340044	\$51	\$47	340046	\$51	\$47
ST-2	2 ³ / ₈ "	1.7	340041	47	42	340043	51	47	340045	51	47	340047	51	47



OT SERIES

Cast aluminum construction with pulley (1⁷/₁₆" outside diameter on OTH, OT1 and OT25; 2" outside diameter on OT2, OT3, OT325 and OT35) on a 1/4" stainless steel axle. Designed to slip over the top of the flagpole and be secured by stainless steel set screws (one 1/4"-20NC on the OTH; three 5/16"-18NC on the OT1, OT2, OT25, OT3, OT325 and OT35). The top of is designed to accept an ornament with a spindle threading of 1/2"-13NC as standard but can be supplied with other sizes of threading if desired. The ornament is secured to the truck with a size 10-32 stainless steel pan head screw. Maximum halyard diameter is 5/16".

For External Halyard Poles • Cap Style • Stationary • Single Pulley

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
OTH	2"	.55	340056	\$21	\$19	340062	\$24	\$22	340068	\$24	\$22	340074	\$24	\$22
OT1	2 ³ / ₈ "	.95	340057	28	24	340063	32	28	340069	32	28	340075	32	28
OT25	2 ¹ / ₂ "	.95	340058	30	26	340064	35	30	340070	35	30	340076	35	30
OT2	2 ³ / ₄ "	1.5	340059	32	28	340065	36	32	340071	36	32	340077	36	32
OT3	3"	1.3	340060	35	30	340066	38	35	340072	38	35	340078	38	35
OT325	3 ¹ / ₄ "	1.2	340343	36	32	340344	42	39	340345	42	39	340346	42	39
OT35	3 ¹ / ₂ "	1.8	340061	39	36	340067	42	39	340073	42	39	340079	42	39



RTC-1 SERIES

Cast aluminum construction with a 2" outside diameter cast pulley on a 1/4" stainless steel axle. The bottom portion of the spindle is designed to fit over the top of the flagpole and is secured with three stainless steel set screws (1/4"-20NC on the RTC-1-2 and RTC-1-138 & 5/16"-18NC on the RTC-1-238). The top is designed to accept an ornament with a spindle threading of 1/2"-13NC as standard but can be supplied with other sizes of threading. The ornament is secured to the truck with a 1/4"-20NC stainless steel set screw. For ease of rotation, product life and strength, these trucks utilize self-lubricating ball bearing assemblies. Maximum halyard diameter is 5/16".

For External Halyard Poles • Cap Style • Revolving • Single Pulley

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
RTC-1-138	1 ³ / ₈ "	1.8	340351	\$77	\$68	340308	\$85	\$76	340309	\$85	\$76	340352	\$85	\$76
RTC-1-2	2"	1.6	340104	77	68	340106	85	76	340108	85	76	340110	85	76
RTC-1-238	2 ³ / ₈ "	1.9	340105	77	68	340107	85	76	340109	85	76	340111	85	76

All trucks on pages 170 thru 173 except the fiberglass trucks can be mixed to achieve the higher quantity pricing.

All bronze colored accessories on pages 168 through 191 are supplied in a dark bronze #313 shade. If medium bronze #312, light bronze #311 or a custom color is desired please call for pricing.

FLAGPOLE TRUCKS & ACCESSORIES



RTC-2 SERIES

Same description as our RTC-1 Series on the previous page, except this series is supplied with two pulleys.

For External Halyard Poles • Cap Style • Revolving • Double Pulley

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
RTC-2-138	1 ³ / ₈ "	2.5	340353	\$77	\$68	340310	\$85	\$76	340311	\$85	\$76	340354	\$85	\$76
RTC-2-2	2"	2.3	340120	77	68	340122	85	76	340124	85	76	340126	85	76
RTC-2-238	2 ³ / ₈ "	2.6	340121	77	68	340123	85	76	340125	85	76	340127	85	76



RTS-1 SERIES

Cast aluminum construction with a 2" outside diameter nylon pulley on a 1/4" stainless steel axle. This truck is designed to be used on flagpoles that have up to a 3 1/2" outside top diameter with female fitting installed. The bottom of the spindle has a 1 1/4" NPT threading and is screwed into the top of the flagpole while the top spindle is designed to accept an ornament with a spindle threading of 1/2"-13NC as standard but can be supplied with other sizes of threading. The ornament is secured to the truck with a 1/4"-20NC stainless steel set screw. For ease of rotation, product life and strength, these trucks utilize self-lubricating ball bearing assemblies. Maximum halyard diameter is 5/16".

For External Halyard Poles • Threaded Type • Revolving • Single Pulley

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
RTS-1-125	3 1/2"	1.9	340136	\$63	\$57	340137	\$69	\$63	340138	\$69	\$63	340139	\$69	\$63



RTS-2 SERIES

Same description as our RTS-1 Series above, except this series is supplied with two pulleys.

For External Halyard Poles • Threaded Type • Revolving • Double Pulley

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
RTS-2-125	3 1/2"	2.6	340144	\$69	\$63	340145	\$74	\$66	340146	\$74	\$66	340147	\$74	\$66



HDT-1 SERIES

Cast aluminum construction with a 3" outside diameter aluminum pulley on 1/2" stainless steel axles. This truck is designed to be used on flagpoles that have up to a 5 1/2" outside top diameter with female fitting installed. The bottom of the spindle has a 1 1/4" NPT threading and is screwed into the top of the flagpole while the top spindle is designed to accept an ornament with a spindle threading of 1/2"-13NC as standard but can be supplied with other sizes of threading. The ornament is secured to the truck with a 1/4"-20NC stainless steel set screw. The truck body rotates on 26 stainless steel ball bearings on cast races. Maximum halyard diameter is 3/8".

For External Halyard Poles • Threaded Type • Revolving • Single Pulley

Note: The revolving arm of this truck can be modified for larger pole top diameters; contact us for a prompt quotation.

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
HDT-1	5 1/2"	8.5	340335	\$147	\$133	340336	\$160	\$143	340337	\$160	\$143	340338	\$160	\$143



HDT-2 SERIES

Same description as our HDT-1 Series above, except this series is supplied with two 3 3/4" pulleys.

For External Halyard Poles • Threaded Type • Revolving • Double Pulley

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
HDT-2	5 1/2"	8.5	340152	\$147	\$133	340153	\$160	\$143	340154	\$160	\$143	340155	\$160	\$143

All trucks on pages 170 thru 173 except the fiberglass trucks can be mixed to achieve the higher quantity pricing.

All bronze colored accessories on pages 168 through 191 are supplied in a dark bronze #313 shade. If medium bronze #312, light bronze #311 or a custom color is desired please call for pricing.

FLAGPOLE TRUCKS & ACCESSORIES



For External Halyard Poles • Threaded Type • Revolving • Double Pulley

EXTRA HEAVY-DUTY SERIES

Cast aluminum construction with 3/8" outside diameter aluminum pulleys on 1/2" stainless steel axles. This truck is designed to be used on flagpoles that have up to a 12 3/4" outside top diameter with female fitting installed. The bottom of the spindle has a 1 1/4" NPT threading and is screwed into the top of the flagpole while the top spindle is designed to accept an ornament with a spindle threading of 1/2"-13NC as standard but can be supplied with other sizes of threading. The ornament is secured to the truck with a 1/4"-20NC stainless steel set screw. For ease of rotation, product life and strength, these trucks utilize stainless steel sealed lubricant ball bearing assemblies. Maximum halyard diameter is 3/8".

MODEL	SPINDLE MATERIAL	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
XHDT	ALUMINUM	9.7	340160	\$620	\$557	340162	\$651	\$588	340164	\$651	\$588	340166	\$651	\$588
XHDT-SS	STAINLESS STEEL	12	340161	1,088	982	340163	1,111	1,003	340165	1,111	1,003	340167	1,111	1,003



For Internal Halyard Poles • Cap Style • Stationary • Single Pulley

IH-1 SERIES

Cast aluminum construction for use on rope style internal halyard flagpoles. A small pulley assembly is added to the inside of a standard outrigger style truck to allow the halyard to feed from inside the flagpole. The pulley assembly has a 1 7/16" outside diameter cast nylon pulley on a 1/4" stainless steel axle and is held in place inside the truck by a 5/16"-18NC stainless steel set screw. The truck has a 2" outside diameter cast nylon pulley on a 1/4" stainless steel axle and is designed to slip over the top of the flagpole and be secured with three 5/16"-18NC stainless steel set screws. The top of the truck will accept an ornament with 1/2"-13NC threading as standard but can be supplied with other sizes of threading. The ornament is held in place by a size 10-32 stainless steel pan head screw. Maximum rope diameter is 5/16".

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
IH-1-3	3"	1.6	340178	\$54	\$49	340180	\$61	\$54	340182	\$61	\$54	340184	\$61	\$54
IH-1-35	3 1/2"	2.3	340179	72	66	340181	82	74	340183	82	74	340185	82	74



For Internal Halyard Poles • Threaded Type • Revolving • Single Pulley

IH-2 SERIES

All of these cast aluminum trucks have a 1 1/4" NPT threaded spindle which screws into the top of the flagpole where a female fitting has been installed. The top of all trucks are designed to accept an ornament with a spindle threading of 1/2"-13NC as standard but can be supplied in other sizes of threading. The ornament is secured to the truck with a 1/4"-20NC stainless steel set screw. The extra large model has stainless steel sealed lubricant bearing assemblies while all other sizes utilize stainless steel ball bearings in both upper & lower bearing races. All sizes are supplied with a stainless steel bushing at the cable exit point except the IHT-3 which has a bronze fitting.

MODEL	TRUCK BASE DIA.	TRUCK HT.	MAX. POLE TOP DIA.	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
					ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
IHT-VR	5"	4 1/2"	3"	3.3	340194	\$175	\$160	340198	\$193	\$175	340206	\$193	\$175	340202	\$193	\$175
IHT-1	6 1/2"	6 1/2"	4"	6.4	340195	270	243	340199	293	264	340207	293	264	340203	293	264
IHT-2	7 1/2"	7 1/4"	5"	8.1	340196	326	293	340200	355	320	340208	355	320	340204	355	320
IHT-3	10 1/2"	8 1/2"	7 1/2"	16	340197	654	589	340201	725	652	340209	725	652	340205	725	652



For Internal Halyard Poles • Threaded Type • Stationary • Single Pulley

IHT-VS SERIES

Cast aluminum construction for use on rope style internal halyard flagpoles. A small pulley assembly is affixed to the inside of the truck housing to allow the halyard to feed from inside the flagpole. The pulley assembly has a 1 7/16" outside diameter cast nylon pulley on a 1/4" stainless steel axle. This truck is designed to be used on flagpoles that have up to a 3 1/2" outside top diameter with female fitting installed. The bottom of the spindle has a 1 1/4" NPT threading and is screwed into the top of the flagpole. The top of the truck will accept an ornament with 1/2"-13NC threading as standard but can be supplied with other sizes of threading. The ornament is secured to the truck with a 1/4"-20NC stainless steel set screw. Maximum rope diameter is 5/16".

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
IHT-VS	3 1/2"	2.4	340312	\$74	\$66	340313	\$82	\$74	340314	\$82	\$74	340315	\$82	\$74

All trucks on pages 170 thru 173 except the fiberglass trucks can be mixed to achieve the higher quantity pricing.

All bronze colored accessories on pages 168 through 191 are supplied in a dark bronze #313 shade. If medium bronze #312, light bronze #311 or a custom color is desired please call for pricing.

FLAGPOLE TRUCKS & ACCESSORIES



For External Halyard Poles • Threaded Type • Revolving • Double Pulley

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
RTS-2-150	3 1/2"	2.8	340170	\$118	\$107	340171	\$132	\$118	340172	\$132	\$118	340173	\$132	\$118

150 SERIES

Cast aluminum construction with 2" outside diameter aluminum pulleys on 3/8" stainless steel axles. This truck is designed to be used on flagpoles that have up to a 4" outside top diameter with female fitting installed. The bottom of the spindle has a 1 1/2" NPT threading and is screwed into the top of the flagpole while the top spindle is designed to accept an ornament with a spindle threading of 1/2"-13NC as standard but can be supplied with other sizes of threading. The ornament is secured to the truck with a 1/4"-20NC stainless steel set screw. The truck body rotates on 26 stainless steel ball bearings on cast races. Maximum halyard diameter is 5/16".



For External Halyard Poles • Threaded Type • Revolving • Double Pulley

MODEL	ITEM #	FITS POLE DIA.	1-5	6+	LBS.
RTSB	340168	4"	\$294	\$273	4.7

BA SERIES

Cast bronze alloy construction with 2" outside diameter nylon pulleys on 1/4" stainless steel axles. This truck is designed to be used on flagpoles that have up to a 4" outside top diameter with female fitting installed. The bottom of the spindle has a 1 1/4" NPT threading and is screwed into the top of the flagpole while the top spindle is designed to accept an ornament with a spindle threading of 1/2"-13NC as standard but can be supplied with other sizes of threading. The ornament is secured to the truck with a 1/4"-20NC stainless steel set screw. For additional ease of rotation, product life and strength, these trucks utilize stainless steel sealed lubricant ball bearing assemblies. Maximum halyard diameter is 5/16".



For External Halyard Poles • Slip Fit Type • Stationary • Single Pulley

WHITE			BRONZE #313			LBS.
ITEM #	1-5	6+	ITEM #	1-5	6+	
340226	\$82	\$74	340227	\$87	\$77	1.4

FIBERGLASS-1 SERIES

Molded fiberglass construction with 3/4" outside diameter nylon pulley on a 3/16" stainless steel axle. The stem of the truck is designed to slip into a 2" inside diameter pole top and is held in place by drilling thru the pole and securing the truck to the pole with an appropriate size bolt or screw (not included). The top of the truck is designed to accept an ornament with a spindle threading of 1/2"-13NC. Maximum halyard size is 1/4".



For External Halyard Poles • Threaded Type • Stationary • Double Pulley

WHITE			BRONZE #313			LBS.
ITEM #	1-5	6+	ITEM #	1-5	6+	
340228	\$82	\$74	340229	\$87	\$77	2.5

FIBERGLASS-2 SERIES

Molded fiberglass construction with 1 1/2" outside diameter nylon pulleys on 1/4" stainless steel axles. The top of the truck is designed to accept an ornament with a spindle threading of 1/2"-13NC as standard but can be supplied with other sizes of threading if desired. The aluminum spindle is threaded 1 1/4" NPT. Maximum halyard diameter is 5/16".



For Internal Halyard Poles • Threaded Type • Stationary • Single Pulley

WHITE			BRONZE #313			LBS.
ITEM #	1-5	6+	ITEM #	1-5	6+	
340232	\$99	\$90	340233	\$104	\$93	2.8

FIBERGLASS-IH SERIES

Molded fiberglass construction with a 1 1/2" outside diameter nylon pulley. This stationary truck is designed to be used on flagpoles that have up to a 3 1/4" outside top diameter with female fitting installed. The spindle has 1 1/4" NPT threading and is screwed into the top of the flagpole. The spindle is hollow allowing the halyard to feed from inside the flagpole. The top of the truck will accept an ornament with a spindle threading of 1/2"-13NC as standard but can be supplied with other sizes of threading. Maximum halyard diameter is 5/16".

All trucks on pages 170 thru 173 except the fiberglass trucks can be mixed to achieve the higher quantity pricing.

All bronze colored accessories on pages 168 through 191 are supplied in a dark bronze #313 shade. If medium bronze #312, light bronze #311 or a custom color is desired please call for pricing.

FLAGPOLE TRUCKS & ACCESSORIES

POLE TOP ADAPTERS



These adapters are used in mounting a truck that has a spindle threading of 1/4" NPT and the pole does not have a threaded top plug installed. The adapter is tapped 1/4" NPT and is designed to slip over the top of the pole and is secured by three 1/4"-20NC stainless steel set screws. Please specify color when ordering. If not specified, silver will be supplied. Pole Top Adapters can be mixed to achieve the higher quantity pricing.

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
PTA-238	2 3/8"	1.1	340238	\$49	\$44	340247	\$54	\$49	340256	\$54	\$49	340265	\$54	\$49
PTA-212	2 1/2"	.90	340239	49	44	340248	54	49	340257	54	49	340266	54	49
PTA-3	3"	1.2	340240	66	61	340249	72	66	340258	72	66	340267	72	66
PTA-312	3 1/2"	1.5	340241	66	61	340250	72	66	340259	72	66	340268	72	66
PTA-4	4"	2.1	340242	79	70	340251	87	77	340260	87	77	340269	87	77
PTA-412	4 1/2"	2.3	340243	79	70	340252	87	77	340261	87	77	340270	87	77
PTA-5	5"	2.7	340244	79	70	340253	87	77	340262	87	77	340271	87	77
PTA-512	5 1/2"	3.2	340245	103	93	340254	112	100	340263	112	100	340272	112	100
PTA-6	6"	4.0	340246	103	93	340255	112	100	340264	112	100	340273	112	100



FLAGPOLE CAPS

Cast aluminum construction designed to slip over the top of the flagpole and be secured with three 1/4"-20NC stainless steel set screws. The top of the cap is designed to accept an ornament with a spindle threading of 1/2"-13NC as standard but can be supplied with other sizes of threading or no threading. Please specify color when ordering. If not specified, silver will be supplied.

MODEL	FITS POLE DIAMETER	LBS.	SILVER			BRONZE #313			WHITE			BLACK		
			ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+	ITEM #	1-5	6+
FC-20	2"	.60	340274	\$18	\$16	340276	\$21	\$19	340278	\$21	\$19	340280	\$21	\$19
FC-212	2 1/2"	.60	340275	21	19	340277	23	21	340279	23	21	340281	23	21



PULLEY & EYEBOLT ASSEMBLIES

Includes Hex Nut, Washer & Lock Washer



MODEL	ITEM #	OVERALL LENGTH	THREAD LENGTH	BOLT THREADING	BOLT MATERIAL	PULLEY HOUSING MATERIAL	PULLEY MATERIAL	MAX. ROPE DIAMETER	1-5	6+	LBS.
DELUXE	340236	4 1/8"	2 3/8"	5/16"-18NC	STAINLESS STEEL	STAINLESS STEEL	NYLON	5/16"	\$17.00	\$16.00	.02
STANDARD	340237	3 1/8"	1"	#8-32NC	ZINC PLATED STEEL	ZINC	ZINC	3/16"	5.40	4.80	.07



NYLON

ROPE PULLEYS

ITEM #	DIA.	WIDTH	MATERIAL	MAXIMUM AXLE DIA.	MAXIMUM ROPE DIA.	1-5	6+	LBS.
340302	1"	3/8"	NYLON	3/16"	1/4"	\$2.80	\$2.50	.01
340303	1 7/16"	11/16"	NYLON	1/4"	5/16"	3.10	2.80	.02
340320	2"	1/2"	NYLON	1/4"	5/16"	3.60	3.20	.04
340304	2"	11/16"	NYLON	1/4"	5/16"	3.90	3.60	.04
340305	3 3/4"	3/4"	ALUMINUM	1/2"	3/8"	21.00	19.00	.45



ALUMINUM



VERTICAL MOUNT PULLEY ASSEMBLIES

Cast aluminum construction with a 1-7/16" outside diameter cast nylon pulley on a 1/4" stainless steel axle. Attaches with two 1/4"-20NC stainless steel flat head screws or two stainless steel straps (screws and/or straps not included). Maximum halyard diameter is 5/16". Not supplied as standard with holes drilled for mounting. Add \$2.00 for drilling.

ITEM #	COLOR	1-5	6+	LBS.
340298	SILVER	\$22	\$20	.60
340299	BRONZE #313	25	23	.60
340300	BLACK	25	23	.60
340301	WHITE	25	23	.60



THREADED TOP PLUGS

Screws into top of pole with 1/4" NPT threading and allows for insertion of ornament with either a 1/2"-13NC or 5/8"-11NC spindle threading.

ITEM #	FOR ORNAMENT SPINDLE SIZE	1-5	6+	LBS.
340306	1/2"-13NC	\$26	\$24	.25
340307	5/8"-11NC	28	25	.25

All bronze colored accessories on pages 168 through 191 are supplied in a dark bronze #313 shade. If medium bronze #312, light bronze #311 or a custom color is desired please call for pricing.